

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/018936 A1

(51) International Patent Classification⁷: B41F 27/10, 5/24

(21) International Application Number:

PCT/IT2003/000516

(22) International Filing Date: 25 August 2003 (25.08.2003)

(25) Filing Language:

Italian

(26) Publication Language:

English

(71) Applicant (for all designated States except US): OF-
FICINE CURIONI S.p.A. [IT/IT]; Strada per Quartiano,
I-26832 Galgagnano LO (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MARCHINI, Giorgio
[IT/IT]; Seconda Strada, 6, I-20090 Seregno MI (IT).

(74) Agents: CONCONE, Emanuele et al.; Società Italiana
Brevetti S.p.A., Via Carducci, 8, I-20123 Milano MI (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PRINTING MACHINE WITH EXTENSIBLE PRINT CYLINDER FOR EASY CHANGE OF THE PRINT SLEEVE



(57) Abstract: A printing machine to work corrugated board and the like includes a print cylinder provided with radial holes (E, E') for emitting compressed air in order to allow the introduction and removal of a print sleeve (S) carrying a print cliché (C), said print cylinder consisting of a fixed shaft (F) on which there is airtightly slidably mounted a mobile cylinder (M) carrying said print sleeve (S), the print cylinder being supported at one end by a dismountable flange with a removable part (R) and by a piston (L) suitable to engage a corresponding seat so to allow the axial movement of said mobile cylinder (M) between a retracted work position and an extended sleeve change position, in which it projects through the machine side to make the change easier, simply by means of the same compressed air used to replace the print sleeve (S).

THIS PAGE BLANK (USPTO)

4/pets

JC20 Rec'd PCT/PTO 09 MAY 2005

"PRINTING MACHINE WITH EXTENSIBLE PRINT CYLINDER FOR EASY
CHANGE OF THE PRINT SLEEVE"

5 The present invention relates to printing machines, and in particular to a
printing machine with extensible print cylinder.

It is known that in the last years in flexographic and rotogravure printing
machines the technology of the so-called "print sleeve" has become widespread,
which sleeve is in practice a light cylinder (usually made of composite material) on
which the print cliché is secured, whereafter the print sleeve is slipped onto the
10 real print cylinder. In this way the replacement of the cliché can take place offline,
thus reducing to a minimum the down time of the machine since the replacement
of the sleeve on the print cylinder is much simpler and faster than that of the cliché
(which requires a very precise positioning for a suitable print quality).

In fact the sleeve is merely slipped onto the cylinder with the aid of
15 compressed air which comes out of radial holes in the cylinder, so as to slightly
expand the sleeve and to make easier the introduction thereof. Once the sleeve has
been positioned, the locking is achieved automatically by cutting off the flow of
compressed air since the sleeve has an inner diameter in interference with the
cylinder, i.e. slightly smaller than the outer diameter of the cylinder.

20 To carry out the sleeve replacement it is therefore necessary for the operator
to access a free end of the print cylinder; at this end the sleeve being used is
removed from the cylinder and still at this same end the replacement sleeve is
slipped onto the cylinder.

However this technology can not be plainly transferred to the field of the
25 machines for working corrugated board and the like (so-called printer slotter,
casemaker or rotary dinker), because the access to the free end of the cylinder to
replace the sleeve is a problem.

In fact in these machines the operator cannot easily reach the end of the
cylinder because the side of the machine has a thickness of 400-600 mm due to the
30 space taken up by the internal mechanisms. Moreover, the room for access is quite
limited by the presence of these mechanisms, and it also implies a certain risk for
the operator who must introduce his arms among the mechanisms and operate in a

- 2 -

quite uncomfortable position and practically blindly.

Therefore the object of the present invention is to provide a printing machine which is free from said drawbacks. This object is achieved by means of a printing machine provided with means for longitudinally extending the print cylinder.
5 Other advantageous features of the present machine are disclosed in the subsequent claims.

The main advantage of the present machine stems from the ease with which the operator can carry out the sleeve replacement, since the cylinder extends towards him through the machine side rather than being he who must introduce his
10 arms in the machine. As a consequence the replacement operation is much easier, faster and safer.

Another significant advantage of this machine stems from the fact that the extension of the cylinder is preferably achieved through a very simple structure by using the same compressed air circuit which already provides the expansion of the
15 sleeve. As a consequence this capacity of the machine does not imply a much greater structural complexity, which positively affects the cost and reliability.

Further advantages and characteristics of the machine according to the present invention will be clear to those skilled in the art from the following detailed description of an embodiment thereof, with reference to the annexed
20 drawings wherein:

Fig.1 is a longitudinal sectional view of the print cylinder in the work position;

Fig.2 is a partial enlarged view of fig.1, showing in greater detail the structure of the mobile portion of the cylinder;

25 Fig.3 is a cross-sectional view along the line III-III of fig.1;

Fig.4 is a cross-sectional view along the line IV-IV of fig.1;

Fig.5 is a view similar to fig.1 of the cylinder in the unlocking phase to start the replacement;

Fig.6 is a view similar to fig.1 of the extended cylinder in the position where
30 the operator can grab the print sleeve; and

Fig.7 is a view similar to fig.1 of the extended cylinder with the sleeve being removed.

- 3 -

With reference to figures 1 to 4, there is seen that in a machine according to the present invention the print cylinder is contained between flanks H, H' with the right flank H' which rigidly supports an internal fixed shaft F on which there is airtightly slidably mounted a mobile cylinder M. Beyond the right flank H' there are arranged the drive members, a protective casing P' and a tube A for the delivery of compressed air which feeds the air to an axial duct T through a relevant rotating joint J.

Through subsequent branches of duct T, the air reaches two series of radial holes E, E' through which it comes out to allow the replacement of sleeve S carrying the cliché C, as previously explained.

The left flank H supports the left end of the print cylinder through a dismountable flange with a removable part R, the cylinder being also locked from below by a piston L which engages a corresponding seat. Beyond the left flank H there is also arranged the knob for the fine adjustment of the centering of the print image in the direction perpendicular to the sheet travel, which knob is accessed through an opening in the protective casing P which is the same opening used to allow the extension of the cylinder.

The simple and effective operation of the present machine is now illustrated with reference also to figures 5 to 7.

Starting from the work condition illustrated in fig.1, when sleeve S has to be replaced first the left support is released, by retracting the bottom piston L and removing the top semiflange R (fig.5).

The extension of the print cylinder is then achieved by feeding compressed air through tube A, joint J and duct T whereby the mobile portion M slides on the fixed shaft F. In this way the end portion of the cylinder comes out through flank H and casing P, and the end of sleeve S can be easily reached by the hands of the operator since it is more or less in the position previously occupied by the adjustment knob (fig.6).

At the end of the preceding phase, the air pressure inside the print cylinder will have reached such a value as to allow the outflow of air through the relevant holes E, E' causing an expansion of sleeve S. Therefore the operator can now effortlessly remove sleeve S from the cylinder and replace it with another sleeve previously prepared with the relevant cliché (fig.7).

Once the new sleeve S is slipped onto the mobile cylinder M for its whole length, still with the aid of the compressed air which continues to come out of the holes, the supply of compressed air is cut off so as to achieve the locking of the

- 4 -

sleeve on the cylinder.

5 The pressure inside the print cylinder is then discharged, so that the mobile part M is free to slide on the fixed shaft F. The operator can thus put it back in position by pushing it inside the machine simply by acting on the knob at the left end.

When the print cylinder is in position, the left support is re-assembled by reinstalling the top semiflange R and by locking with piston L from below.

10 It is clear that the above-described and illustrated embodiment of the machine according to the invention is just an example susceptible of various modifications. In particular, the releasable means which support the free end of the cylinder may be different from the removable semiflange R and the locking piston L, for example two or more pistons or other locking means which can be retracted to allow the extension of the cylinder.

15 Similarly, the extension of the cylinder may be achieved through means different from compressed air, such as an axial pusher, a wormscrew or the like.

- 5 -

CLAIMS

1. Printing machine including a print cylinder provided with radial holes (E, E') for emitting compressed air in order to allow the introduction and removal
5 of a print sleeve (S) carrying a print cliché (C), characterized in that said print cylinder consists of a fixed shaft (F) on which there is slidably mounted a mobile cylinder (M) carrying said print sleeve (S), in that the print cylinder is supported at one end by releasable support means suitable to allow the axial movement of said mobile cylinder (M), and in that it includes means for axially moving the mobile
10 cylinder (M) between a retracted work position and an extended sleeve change position in which it projects through the machine side.

2. Printing machine according to claim 1, characterized in that the mobile cylinder (M) is airtightly slidably mounted on the fixed shaft (F) and its axial movement is achieved by means of the same compressed air used to replace the
15 print sleeve (S).

3. Printing machine according to claim 1 or 2, characterized in that the releasable support means consist of a dismountable flange with a removable part (R), and of a piston (L) suitable to engage a corresponding seat in the cylinder.

BEST AVAILABLE COPY




Fig. 1




Fig. 4





Fig. 3

JC20 Rec'd PCT/PTO 09 MAY 2005

BEST AVAILABLE COPY



JC20 Rec'd PCT/PTO 09 MAY 2005

BEST AVAILABLE COPY




Fig. 5




Fig. 6

JC20 Rec'd PCT/PTO 09 NOV 2009

BEST AVAILABLE COPY




Fig. 7

JC20 Rec'd PGT/PTC 9 MAY 2005

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT 03/00516

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B41F27/10 B41F5/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B41F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 802 975 A (PREM WOLFGANG ET AL) 8 September 1998 (1998-09-08)	1,2
Y	column 4, line 26 - line 38; figures	3
Y	US 5 241 905 A (GUARALDI GLENN A ET AL) 7 September 1993 (1993-09-07) abstract	3
A	US 6 142 073 A (VAN RYZIN WILLIAM J ET AL) 7 November 2000 (2000-11-07) abstract; figures	1-3
A	US 6 360 662 B1 (BUSSHOFF MARIO) 26 March 2002 (2002-03-26) abstract; figures	1-3
A	US 4 913 048 A (TITTEMEYER UDO) 3 April 1990 (1990-04-03) abstract; figures	1-3

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 March 2004

Date of mailing of the international search report

29/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gavaza, B

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 03/00516

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5802975	A	08-09-1998	DE 4341246 C1	23-02-1995
			CA 2137089 A1	04-06-1995
			FR 2713142 A1	09-06-1995
			GB 2284389 A , B	07-06-1995
			IT RM940761 A1	05-06-1995
			JP 2638754 B2	06-08-1997
			JP 7195669 A	01-08-1995
US 5241905	A	07-09-1993	DE 4332364 A1	28-04-1994
			DE 59302256 D1	23-05-1996
			EP 0596244 A1	11-05-1994
			JP 3117592 B2	18-12-2000
			JP 6191007 A	12-07-1994
			US RE35646 E	04-11-1997
US 6142073	A	07-11-2000	BR 0003458 A	03-04-2001
			CA 2313885 A1	20-02-2001
			DE 1080890 T1	06-03-2003
			EP 1080890 A1	07-03-2001
			JP 2001096716 A	10-04-2001
US 6360662	B1	26-03-2002	AU 4177301 A	03-10-2001
			BR 0109298 A	24-12-2002
			CA 2399718 A1	27-09-2001
			CN 1443114 T	17-09-2003
			CZ 20022687 A3	15-01-2003
			EP 1263592 A2	11-12-2002
			WO 0170505 A2	27-09-2001
			US 6276271 B1	21-08-2001
			US 2002023562 A1	28-02-2002
US 4913048	A	03-04-1990	DE 3543704 A1	19-06-1987
			AT 93772 T	15-09-1993
			BR 8606104 A	15-09-1987
			CS 8609151 A2	12-09-1990
			DD 250900 A5	28-10-1987
			DE 3650281 D1	27-04-1995
			DE 3688969 D1	07-10-1993
			EP 0225509 A2	16-06-1987
			EP 0549936 A1	07-07-1993
			ES 2044831 T3	16-01-1994
			JP 2519225 B2	31-07-1996
			JP 62218130 A	25-09-1987
			KR 188463 B1	01-06-1999
			SU 1828434 A3	15-07-1993
			US RE34970 E	20-06-1995